

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 281 661 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
05.02.2003 Bulletin 2003/06

(51) Int Cl.7: **B67C 3/24, B08B 9/42**

(21) Application number: **02016609.6**

(22) Date of filing: **25.07.2002**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR  
IE IT LI LU MC NL PT SE SK TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:  
• **Baini, Stefano**  
43013 Langhirano (IT)  
• **Preti, Fabrizio**  
43015 Noceto (Parma) (IT)

(30) Priority: **31.07.2001 IT PR20010050**

(74) Representative: **Gotra, Stefano**  
**Bugnion S.p.A.**  
Via Garibaldi 22  
43100 Parma (IT)

(71) Applicant: **Sig Simonazzi Beverage S.p.A.**  
43100 Parma (IT)

(54) **Gripper, in particular for holding containers**

(57) Gripper (1), in particular for holding containers, of the type comprising a pair of mutually facing jaws (2), fastened to a support structure (3) and movable between a first operative configuration of holding the containers and a second operative configuration of releas-

ing the containers. The gripper (1) originally comprises at least a rigid element (4) to connect said jaws (2) kinematically and allow its substantially simultaneous and controlled operation. Said rigid element (4) is substantially a connecting rod having each of its ends hinged to a corresponding jaw (2).




FIG. 3

## Description

[0001] The present invention relates to a gripper, in particular for holding containers, of the type comprising a pair of mutually facing jaws, fastened to a support structure and movable between a first operative configuration for holding the containers and a second operative configuration for releasing said containers and actuating means operatively active on at least one of said jaws.

[0002] In bottling plants, rotary machines are provided, such as filling and/or rinsing machines, fitted with a plurality of stations positioned on the periphery of a carousel and each equipped with a gripper, in such a way that they can simultaneously process a plurality of containers.

[0003] DE29501897 discloses grippers for a star conveyor constituted by jaws that open and close with motions in a horizontal plane, operated by a command device comprising a cam able to rotate between the counter-braces of the jaws to spread them or to allow them to approach each other if a return is present which tends to bring the jaws to the opened position.

[0004] The grippers briefly described above suffer from the drawback of having a very complex device for actuating the jaws.

[0005] Also known are grippers constituted by substantially automatic gripping elements, which do not need to be opened or closed by means of springs or cams. Said gripping elements are so shaped as to comprise a dual pair of jaws able to grip the bottles in the mouth area below the neck and in the central area of the body.

[0006] During the operation of the plant, the containers are forced to enter the jaws slightly forcing them to open in automatic fashion, whilst the same containers are forced to exit the jaws by a conventional star conveyor.

[0007] The grippers briefly described above suffer from the drawback of having a rather complex gripping element formed by a dual pair of jaws which are also completely unsuited for gripping containers made of plastic material, such as PET bottles. Such bottles cannot tolerate a grip on the central part of the body, with its poor rigidity, or a grip below the neck as in the solution described above.

[0008] An aim of the present invention is to eliminate the aforesaid drawbacks making available a gripper, in particular for holding containers, that is structurally simple and easy to operate.

[0009] Another aim of the present invention is to propose a gripper that is able to hold containers made of any materials, with particular regard for PET and glass.

[0010] Said aims are fully achieved by the gripper, in particular for holding containers, of the present invention, which is characterised by the contents of the claims set out below and in particular in that it comprises at least a rigid element in order kinematically to connect

the jaws and allow a substantially simultaneous and controlled actuation thereof.

[0011] This and other characteristics shall become more readily apparent from the description that follows of a preferred embodiment illustrated, purely by way of non limiting example, in the accompanying drawing tables, in which:

- Figure 1 shows an axonometric view of a gripper according to the present invention;
- Figure 2 shows a top view of the gripper of Figure 1;
- Figure 3 shows a bottom view of the gripper of Figure 1;
- Figure 4 shows a carousel provided with a plurality of grippers according to the invention.

[0012] With reference to the figures, the gripper, in particular for holding containers, is globally indicated with the reference number 1.

[0013] This gripper comprises a pair of mutually facing jaws 2, fastened to a support structure 3 and movable between a first operative configuration for holding the containers and a second operative configuration for releasing them, in particular operating on the neck of the containers.

[0014] Said gripper originally comprises at least a rigid element 4, preferably a rod-like body, to connect the jaws 2 kinematically and allowing their substantially simultaneous and controlled actuation. Said rigid element 4 is substantially a connecting rod having each of its ends hinged to a corresponding jaw.

[0015] Each jaw 2 is fastened to the support structure 3 by means of at least a hinge 5 and it is movable by rotation about a substantially vertical axis passing through the hinge itself. In the illustrated example, the support structure 3 whereon the gripper 1 is fastened is a rotating platform able to be used in rotary machines, in particular filling machines.

[0016] Each gripper 1 fastened to the support structure 3 is associated to actuating means comprising at least a cam (not shown herein) operatively active on only one of the jaws 2 to induce its rotation about the axis passing through the hinge 5. In particular, the jaw associated to the cam comprises at least a pin 6 positioned in correspondence with an end of said jaw and so shaped as to slide on said cam. Also present is at least an elastic element 7, preferably a spring, to maintain and/or bring back to the holding configuration the jaws 2 after the containers are released.

[0017] The pin 6 of each gripper 1 fastened to the support structure 3 is inserted within a corresponding slot 6a that allows its translation, thereby determining the rotation of the jaw about the axis that passes through hinge 5.

[0018] In an embodiment not illustrated herein, it is possible for each jaw 2 to be provided with at least an insert made of a material capable of absorbing impacts, preferably rubber, in order to allow holding fragile con-

tainers, such as glass bottles.

[0019] The operation of the invention is as follows.

[0020] The support structure 3, during its motion, alternatively brings the pins 6 of the gripper 1 in contact with the cam. In this way, the pins, sliding on the cam, translate within the corresponding slots 6a, causing the rotation of one of the jaws of each gripper about the axis passing through the hinges 5.

[0021] The motion of said jaw is transmitted to the other jaw of a same gripper by means of the rigid element 4, thereby determining the opening of the gripper 1. In particular, the rigid element 4 works substantially in traction during the opening of the gripper and substantially in compression during its closure.

[0022] Continuing with the rotation, the support structure 3 causes the pins 6 to move away from the cam, determining the closure of the gripper 1 around the neck of a container, by effect of the return force exerted by the elastic element 7.

[0023] The invention achieves important advantages.

[0024] First, the gripper according to the invention is structurally simple to build and easily operated. The actuation of the gripper is associated to one jaw only and the motion is transmitted to the other by means of the rigid element, thereby guaranteeing synchrony and symmetry in the opening and closing movements.

[0025] An additional advantage is represented by the fact that a gripper according to the invention is able to hold, acting on the neck, containers made of any material, with particular regard to PET and glass containers.

4. Gripper as claimed in claim 3, **characterised in that** it is associated to actuating means comprising at least a cam operatively active on only one of said jaws (2) to induce its rotation about said axis passing through the hinge (5).

5. Gripper as claimed in claim 4, **characterised in that** said jaw (2) associated to the cam comprises:

at least a pin (6) positioned in correspondence with an end of said jaw (2) and so shaped as to slide on said cam;

at least an elastic element (7) to maintain the jaws (2) and/or bring them back in holding configuration after the containers are released.

6. Gripper as claimed in claim 1, **characterised in that** each jaw (2) is provided with at least an insert made of a material capable of absorbing impacts to allow the holding of fragile containers.

7. Machine for processing containers, **characterised in that** it comprises at least a gripper (1) as claimed in any of the previous claims.

## Claims

1. Gripper (1), in particular for holding containers, of the type comprising:

a pair of mutually facing jaws (2), fastened to a support structure (3) and movable between a first operative configuration of holding the containers and a second operative configuration of releasing the containers,

**characterised in that** it comprises at least a rigid element (4) to connect said jaws (2) kinetically and allow their substantially simultaneous and controlled operation.

2. Gripper as claimed in claim 1, **characterised in that** said rigid element (4) is substantially a connecting rod having each of the ends hinged to a corresponding jaws (2).

3. Gripper as claimed in claim 1, **characterised in that** each jaw (2) is fastened to the support structure (3) by means of at least a hinge (5) and is movable by rotation about a substantially vertical axis passing through the hinge (5) itself.

FIG. 1





FIG. 2





FIG. 3

FIG. 4





European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 02 01 6609

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 577 569 A (AVE SPA) 5 January 1994 (1994-01-05) * column 3, line 3 - line 21; figure 5 *	1-3,6,7	B67C3/24 B08B9/42
X	EP 0 940 340 A (GD SPA) 8 September 1999 (1999-09-08) * figure 5 *	1,2,7	
X	EP 1 028 075 A (RONCHI MARIO S R L) 16 August 2000 (2000-08-16) * paragraph '0010!'; figure 5 *	1,2,7	
X	EP 0 854 102 A (S B R S R L) 22 July 1998 (1998-07-22) * figures 4,5 *	1,3-5	
X	WO 99 51514 A (SASIB LABELLING MACHINERY S P ; SASIB SPA (IT); PRETI FABRIZIO (IT)) 14 October 1999 (1999-10-14) * page 5, line 9 - line 10; figure 6 *	1,6,7	
X	US 4 363 649 A (YAMATO YOSHIHIRO ET AL) 14 December 1982 (1982-12-14) * figure 2 *	1	
X	DE 197 40 890 A (KETTNER GMBH) 25 March 1999 (1999-03-25) * figure 2 *	1	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7) B67C B08B B65G
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>4 November 2002</b>	Examiner <b>Martínez Navarro, A.</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 01 6609

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-11-2002

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0577569	A	05-01-1994	IT	PD920080 U1	30-12-1993
			AT	137199 T	15-05-1996
			DE	69302333 D1	30-05-1996
			DE	69302333 T2	31-10-1996
			DE	577569 T1	14-06-1995
			DK	577569 T3	29-07-1996
			EP	0577569 A1	05-01-1994
			ES	2060573 T1	01-12-1994
			GR	3020322 T3	30-09-1996
			HK	1007547 A1	16-04-1999
			RO	111562 B1	29-11-1996
EP 0940340	A	08-09-1999	IT	B0980127 A1	06-09-1999
			DE	69900221 D1	27-09-2001
			DE	69900221 T2	02-05-2002
			EP	0940340 A1	08-09-1999
			ES	2162500 T3	16-12-2001
			PT	940340 T	30-01-2002
			US	6186313 B1	13-02-2001
EP 1028075	A	16-08-2000	IT	MI990253 A1	10-08-2000
			EP	1028075 A1	16-08-2000
			US	6345713 B1	12-02-2002
EP 0854102	A	22-07-1998	IT	MI970076 A1	16-07-1998
			AU	730116 B2	22-02-2001
			AU	5206298 A	23-07-1998
			DE	69801239 D1	06-09-2001
			DE	69801239 T2	02-05-2002
			EP	0854102 A1	22-07-1998
			ES	2159913 T3	16-10-2001
			US	6079541 A	27-06-2000
WO 9951514	A	14-10-1999	IT	PR980021 A1	07-10-1999
			EP	1070013 A1	24-01-2001
			WO	9951514 A1	14-10-1999
US 4363649	A	14-12-1982	AU	554222 B2	14-08-1986
			AU	7625281 A	21-04-1983
			CA	1149638 A1	12-07-1983
DE 19740890	A	25-03-1999	DE	19740890 A1	25-03-1999
			DE	29723881 U1	22-04-1999

**THIS PAGE BLANK (USPTO)**